

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

P	roi	Þ	ct	
	ιUj	e	υı	1

Model # : Item # :

Qty :

Available W/H :

Approval :

Club Top Beer Dispensers

Underbar Equipment Super Deluxe Series

<section-header>

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Hydrocarbon refrigerants (R-600a)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Forced air cooling system

Fast cooling and balanced temperature throughout the cabinet.

Stainless steel cabinet construction

Super Deluxe (SD) models boast a stainless steel exterior (except galvanized steel back and bottom). SB models have an attractive wear-resistant black vinyl exterior. Heavy gauge stainless steel countertop and club top lids are perfect for sanitation and durability. The interior is stainless steel except galvanized steel top. Spacious inside construction with 32" inner height accommodates various sizes of beer kegs. Turbo Air Club Top model guarantees the utmost in cleanliness and long product life. It also adds a touch of style to the most refined setting.

- High-density polyurethane insulation The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.
- 3" diameter stainless steel insulated beer towers
- Comes standard with a four-way tapper manifold
- Club top (TCB) models provide easy access to the interior area

Club Top is a combined functional cabinet of direct draw cold beer dispenser and glass chiller. This convenient model provides easy access to interior storage area of the refrigerator for chilled beer glasses.

- Ergonomically designed doors
- Easy to glide stainless steel club top lids
- Side mount compressor unit
- Club top beer dispenser holds 33°F ~ 38°F for the best in beverage preservation

life. It also adds a touch of style to the most refined setting.				NATURAL (Source) Intertek		
Model	Swing Door	1/2 Barrels	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^+$ (inches)
TCB-2SD-N6 TCB-2SB-N6	2 2	2 2	1/5 1/5	1.3 1.3	355 355	587/8 x 271/4 x 385/8 587/8 x 271/4 x 385/8

* Depth does not include 2" for rear spacers. † Height does not include 5" for caster height. Height does not include 15-1/8" for draft arm.

Club Top Beer Dispenser

Model : TCB-2SD/SB-N6

ELECTRICAL DATA				
Voltage		115/60/1		
Plug Type		NEMA 5-15P		
Full Load Amperes		1.3		
Compressor HP		1/5		
Refrigerant		R-600a		
Cord Length (ft.)		8.5		
DIMENSION	AL DATA			
Net Capacity	(1/2 Barrels)	2		
	(cu.ft.)	20.9		
Ext. Length Overall (in.)		587/8 (1494mm)		
Ext. Depth Overall (in.)*		271/4 (692mm)		
Ext. Height Overall (in.)†		385/8 (980mm)		
Net Weight (lbs.)		335		
Gross Weight (lbs.)		355		
# of Swing Door		2		
# of Casters		6EA		

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2" for rear spacers.

† Height does not include 5" for caster height. Height does not include 15-1/8" for draft arm.

WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


- Anti-corrosion coated evaporator
- Double faucet beer tower standard
- Door locks standard
- Self-contained system
- 4" dia. swivel casters standard
- 2" dia. casters available (optional)
- 6" height adjustable legs available (optional)
- Triple faucet beer tower available (optional)

OPTIONAL ACCESSORIES :


- □ 2" caster for underbar series, ½" diameter: P0165B0100 (non-brake), P0165B0110 (w/ brake)
- G" adjustable stainless steel leg: P0121P0100
- Triple faucet draft tower: 153A-3

PLAN VIEW


(unit : inch)



PLAN VIEW



FRONT VIEW



Ver.20171025

ENERGY STAR®

- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- Warranty: 800-381-7770 AC: 888-900-1002



SPEC

NATURAL Refrigerant



